

Professional Cleaning Machines



One Stop Solution for Professional Cleaning





Optima 85B



Innova 75BM



Omnia 32B



Media 75BT

Technical Information		Optima 85B	Innova 75BM	Omnia 32B	Media 75BT
Working Capacity	Sqm/h	5500	4500	3320	3800
Working Width	mm	850	750	830	760
Power Supply / Traction	V	24 / aut.	24 / aut.	36 / aut.	24 / aut.
Solution Tank	Lt	160	110	105	85
Recovery Tank	Lt	160	125	115	95
Brush Pressure	Kg	100	30	80	30-50
Weight (empty)	Kg	320	223	240	150
Dimensions (LxHxW)	mm	1777 x 1265 x 892	1495 x 1320 x 680	1650 x 1120 x 850	1495 x 1065 x 800



Simpla 50B



Abila 20B



Vispa 35B



Vispa 35E

Technical Information		Simpla 50B	Abila 20B	Vispa 35B	Vispa 35E
Working Capacity	Sqm/h	1785	1750	1000	800
Working Width	mm	510	500	350	350
Power Supply / Traction	V	24 / semi aut.	24 / semi aut.	12 / semi aut.	Electric / semi aut.
Solution Tank	Lt	50	33	10	8
Recovery Tank	Lt	55	40	10	10
Brush Pressure	Kg	25	20	20	18
Weight (empty)	Kg	86	72	42	35
Dimensions (LxHxW)	mm	1300 x 1060 x 560	1160 x 960 x 455	682 x 1018 x 440	620 x 1050 x 440



RA55B40



RA55K40

Technical Information		RA55B40	RA55K40
Working Capacity	Sqm/h	2200	2200
Working Width	mm	550	550
Power Supply / Traction	V	24 / semi aut.	Electric / semi aut.
Solution Tank	Lt	40	40
Recovery Tank	Lt	40	40
Brush Pressure	Kg	24	46
Weight (empty)	Kg	77	70
Dimensions (LxHxW)	mm	1200 x 870 x 550	1035 x 815 x 525

SCRUBBER เครื่องขัดล้างพื้น



E500S



E500E

Technical Information		E500S	E500E
Rate Power Input	W	1800	1200
Working Width	mm	500	500
Power Supply	V	230	230
Brush Speed	RPM	140	140
Power Cable	m	12	12
Weight	Kg	50	45

Optional Accessories:
 - Add-On Weight 20 KG (For E500S only)
 - Tank Assy ES BG





CM70HS



CM50HS



Proglazer



P1600

Technical Information		CM70HS	CM50HS	Proglazer	P1600
Working Capacity	Sqm/h	4140	1785	2300	-
Working Width	mm	690	510	559	510
Power Supply		36V Battery	24V Battery	17HP Kawasaki	220V Electric
Brush Speed	RPM	1500	1400	2000	1600
Brush Pressure	Kg	10-15	10-15	18	6.8
Vacuum System		Yes	Yes	No	No
Weight (empty)	Kg	336	134	114	40
Dimensions (LxHxW)	mm	1685 x 1370 x 680	1400 x 960 x 570	1400 x 905 x 560	902 x 1130 x 584



Ronda



Mille



Boxer



Otto

Technical Information		Ronda	Mille	Boxer	Otto
Working Capacity	Sqm/h	19900	19900	12400	9800 / 7000
Working Width	mm	1600 (with 2 brushes)	1700 (with 2 brushes)	1550 (with 2 brushes)	1300 (with 2 brushes)
Power		Diesel	Diesel	Diesel / Battery	Diesel / Petrol / Battery
Hopper Capacity	Lt	310	350	240	130
Filtering Surface	Sqm	8	13.5	9.2	6
Hopper Unloading		Hydraulic	Hydraulic	Hydraulic	Hydraulic
Weight (empty)	Kg	1270	970	825 / 820	529 / 518 / 760
Dimensions (LxHxW)	mm	2620 x 2130 x 1030	1970 x 1480 x 1340	1900 x 1380 x 1190	1640 x 1510 x 1070



Dust Buster System eliminates dust picked up by side brushes to improve cleaning performance and operator's comfort.



Atom Plus



Slalom



Alfa H



Alfa E

Technical Information		Atom Plus	Slalom	Alfa H	Alfa E
Working Capacity	Sqm/h	7315	6050	2800	2800
Working Width	mm	1330 (with 2 brushes)	863	700	700
Power		Petrol / Battery	Battery	Petrol	Battery
Hopper Capacity	Lt	95	50	43	43
Filtering Surface	Sqm	6	3	2.25	2.25
Hopper Unloading		Manual	Manual	Manual	Manual
Weight (empty)	Kg	262 / 225	185	56	48
Dimensions (LxHxW)	mm	1390 x 1140 x 1010	1230 x 1120 x 780	1230 x 990 x 680	1230 x 990 x 680

Smart Traction System combines two brushes to sweep the floor, while also move the machine forward. It allows users to control the machine with extremely light effort.

Dust Buster System eliminates dust picked up by side brushes to improve cleaning performance and operator's comfort.



PW-H80



PW-H40/4



PW-C90



Total Stop D - Delayed Total Stop : This safety system shuts the machine down after 30 seconds of inactivity and restarts it automatically as soon as the trigger gun is activated.



Power Boil : IPC latest high efficiency boilers. Designed for a long working life, the cylinders and internal components are made entirely from stainless steel. The double pass coils are made from special corrosion and oxidation resistant steel tubing.



Total Stop ITS - Intelligent Total Stop : This safety system shuts the machine down after 10 seconds of inactivity and restarts it automatically as soon as the trigger gun is activated. After 18 minutes of inactivity, the system shuts the machine down completely. It also warns if the water circuit is leaking of the fuel or water softener has run out.



Power Pump : The main characteristics of the new IPC crankshaft pump are top performance, excellent resistance to thermal shock, a long working life and ease of maintenance.

Technical Information		PW-H80	PW-H40/4	PW-C90
Type		Hot & Cold	Hot & Cold	Cold
Remote control		Total Stop ITS	Total Stop D	Total Stop D
Pump		Power Pump	Power Pump	Power Pump
Boiler		Power Boiler	Power Boiler	-
Pressure	Bar	40 - 200	40 - 130	30 - 130
Flow Rate	l/h	500 - 1000	300 - 600	300 - 600
Voltage	Ph / V / Hz	3 / 400 / 50	1 / 230 / 50	1 / 230 / 50
Absorbed Power	Kw	7.2	3.3	3.2
Speed	RPM	1400 (4-Pole)	1400 (4-Pole)	1400 (4-Pole)
Weight (empty)	Kg	146.6	129.8	41.9
Detergent Tank	Lt	25	20	7.5
Dimensions	mm	1090 x 700 x 870	1050 x 750 x 900	730 x 480 x 880



ROKY



ISSA 103



ISSA 203



LEO



FREE 202

Technical Information		ROKY	ISSA 103	ISSA 203	LEO	FREE 202
N. of Motor		1	1	1	1	1
Motor	W Max	1150	1150	1150	1300	1300
Water Lift	mm H ₂ O	2410	2410	2410	2870	2970
Air Flow	Cu.m/h	195	195	195	210	208
Tank Capacity	Lt	29	15	26	12.5	19
Weight	Kg	7.4	8.5	9.0	8.0	8.7
Motor Type		2 stage	2 stage	2 stage	1 stage	1 stage
Application		Professional	Professional	Professional	Basic	Basic

SPECIAL DRY VACUUM เครื่องดูดฝุ่นชนิดพิเศษ



SHAKE



ECOSPITAL

Technical Information		SHAKE*	ECOSPITAL	WHITE R	150BV
N. of Motor		1	1	1	1
Motor	W Max	1400	1300	1000	1300
Water Lift	mm H ₂ O	2400	2870	2280	2243
Air Flow	Cu.m/h	220	210	170	154
Tank Capacity	Lt	15 / 41	27	32	5
Weight	Kg	20	9.2	13.6	4.85
Filtration		1 micron	0.3 micron	0.3 micron	0.3 micron
Filter Type		Washable Cartridge	HEPA	HEPA	Micron
Motor Type		2 stage	1 stage	2 stage	1 stage
Application		Professional	Professional	Professional	Professional

* Model SHAKE is equipped with automatic and manual vibration shaker, and electrical socket for electrical tools.

WET & DRY VACUUM เครื่องดูดฝุ่น ดูดน้ำ



ISSA 640



ISSA 629



ISSA 429



ISSA 515



SUPERCONDOR

Technical Information		ISSA 640	ISSA 629	ISSA 429	ISSA 515	SUPER CONDOR
N. of Motor		3	2	2	1	1
Motor	W Max	3300	2400	2400	1200	1200
Water Lift	mm H ₂ O	2470	2470	2470	2470	2470
Air Flow	Cu.m/h	630	420	420	210	210
Tank Capacity	Lt	89	78	90	41	26
Weight	Kg	28.0	24.0	24.0	10.0	9.0
Motor Type		2 stage	2 stage	2 stage	2 stage	2 stage
Application		Professional	Professional	Professional	Professional	Professional

WET & DRY VACUUM เครื่องดูดฝุ่น ดูดน้ำ



VEGAS 429



FREE 440



FREE 429



FREE 515

Technical Information		VEGAS 429*	FREE 440	FREE 429	FREE 515
N. of Motor		2	3	2	1
Motor	W Max	2600	3500	2800	1500
Water Lift	mm H ₂ O	2380 / 3800	2230	2230	2230
Air Flow	Cu.m/h	400 / 220	710	475	237
Tank Capacity	Lt	62	62	62	26
Weight	Kg	24.0	26.0	24.0	9.0
Motor Type		1 stage	1 stage	1 stage	1 stage
Application		Professional	Basic	Basic	Basic

* Model VEGAS 429 is equipped with **FLOWMIX SYSTEM**.



CADET 7

Technical Information		CADET 7	CLIP	LAVA
Vacuum Motor	W Max	1119	1200	1200
Solution Pump	Bar	4.9	2.5	2.0
Solution Tank	Lt	26	11.4	6.2
Recovery Tank	Lt	26	50	27
Brush Size	mm	380	-	-
Weight	Kg	39	11.5	10
Motor Type		3 stage	2 stage	2 stage
Application		Professional	Semi Professional	Basic



CLIP



LAVA



CRI Approved



LEED Qualified IEQ Credit 3.4

CARPET VACUUM เครื่องดูดฝุ่นตะกรวยพรม



WAVE

Technical Information		WAVE	BS36
Vacuum Motor	W Max	2 x 802	1300
Brush Motor	W	186	175
Brush Size	mm	710	360
Filter Bag	Lt	35	5
Weight	Kg	43	7.9
Power Cable	m	23	10
Application		Professional	Professional



BS36



CRI Approved



LEED Qualified IEQ Credit 3.4

*IEQ Credit 3.4 = Environmentally friendly equipment purchasing and maintenance of equipment.



RAPID AIR



WINDY 3 SPEED

Technical Information		Rapid Air	Windy 3 Speed
Motor	W	750	900
Speed Setting		3 speed	3 speed
Voltage	V	220 - 240	220 - 240
Angle Position		0°/45°/90°	0°
Power Cable	m	12	7
Weight	Kg	15	19

STONE CARE SYSTEM เครื่องพื้พู่พื้หิน



LEVIGHETOR



KROMA

Technical Information		Levighetor	Kroma
Working Width	mm	430	450
Max Power	HP	4.0	2.5
Basic Speed	RPM	200	155
Grinding Disc Speed	RPM	1000	900
Water Tank	Lt	18	18
Weight with Grinding Tool	Kg	109	65
Grinding Tool		Planetario 3 x 100 mm	Planetario 3 x 100 mm





STEAMER JET M



STEAMY PLUS

Technical Information		STEAMER JET M	STEAMY PLUS
Boiler Volume	Lt	3.5	2.7
Working Pressure	Bar	5	5
Steam Temperature	C	150	140
Steam Volume	g / min	40 / 80 / 100	0 - 80
Absorbed Power	W	3500	3000



Standard Equipment STEAMER JET M



Standard Equipment STEAMY PLUS

SPECIAL AREA CLEANING เครื่องทำความสะอาดเฉพาะทาง



FOAMTEC 30

FOAMTEC 30 is the **Foam-Rinse-Vacuum system**, a revolutionary system to clean and sanitize public restrooms and other areas, by foaming, rinsing and vacuuming, using a single machine.

The cleaning and sanitizing process is carried out through four stages:

1. Foam spraying on all surfaces (walls, sanitary fixtures, showers, panes)
2. Foam chemical action against dirt and bacteria
3. Rinsing with fresh water, to remove foam residual from the surfaces
4. Vacuuming of residual water from floor

*Performance: 15 mins / room with 50 sqm. + 10 sanitary fixtures



CIMEX X46

The Cimex X46 Escalator Cleaner is designed to help reduce operating costs and dramatically improve the appearance of escalator / travelator. Automatic brush height adjustment for uniform performance. Powerful vacuum dust pick up with quick change disposable bags. Portable for multi-escalator sites. Very easy to use and minimal training required for increased efficiency. Powered rotating brushes for fast, effective cleaning. Choice of brushes to suit soiling level. Brush change is quick and easy.



Y.N.C. (Thailand) was established in 1985 as one of the first suppliers offering world-class cleaning machines and equipment in Thailand. Starting with only 2 product lines at its inception, YNC now provides over 20 product lines of cleaning machines and equipment, which enables YNC to serve and satisfy the various needs of its customers.

For nearly 30 years, YNC has been recognized as one of the best suppliers for its excellent products and after-sale services. We take pride in our reputation, as we value building long-term relationships with our clients. We will continue to endeavor to provide best-in-breed products through our network of global cleaning machine and equipment manufacturers, as well as provide high quality services to our customers, which has earned us our reputation today.

YNC is able to maintain its leadership position by continuously introducing innovative products and making sure our clients can take advantage of the technologies we offer. Not only is YNC prepared to readily serve our clients through our wide array of products, we also provide advisory services to help our customers navigate through any cleaning requirements that they may have, in an ever-changing market.

As our company motto states, we are committed to provide
"One Stop Solutions"
for all our customers' professional cleaning needs.

Y.N.C. (Thailand) Co., Ltd.

366 Ladprao 94, Ladprao Road, Plubpla, Wangtonglarng, Bangkok 10310 THAILAND

Tel. 02 934 4636 ~ 40 Fax. 02 559 2900

E-mail: info@ync.co.th Website: www.ync.co.th